rev:6/8/2005 14136

PAGE: 1 ACCT: 580773001 DATE: 07/18/06 CAT NO: A258500 INDEX: D61958637 PO NBR: NA Material Safety Data Sheet Propionic acid MSDS# 19750 Section 1 - Chemical Product and Company Identification MSDS Name: Propionic acid Catalog Numbers: AC149300000, AC149300010, AC149300025, AC149300050, AC220130000, AC22013001 AC220130010, S80149, S801491, A258-500, A258500LC, A258N119, NC9278797 Carboxyethane; Ethanecarboxylic acid; Ethylformic acid; Methylacetic acid; Metacetonic acid; Propanoic acid; Propanoic acid grain preserver; Psuedoacetic acid. Company Identification: Fisher Scientific One Reagent Lane Fair Lawn, NJ 07410 For information in the US, call: 201-796-7100 Emergency Number US:201-796-7100 CHEMTREC Phone Number, US: 800-424-9300 Section 2 - Composition, Information on Ingredients 79-09-4 CAS# : Chemical Name: Propionic acid 99 201-176-3 EINECS#: Hazard Symbols: Risk Phrases: 34 Section 3 ~ Hazards Identification EMERGENCY OVERVIEW Danger! Flammable liquid and vapor. Causes eye and skin burns. Causes digestive and respiratory tract burns. Target Organs: Respiratory system, gastrointestinal system, eyes, skin. Potential Health Effects Eye: May result in corneal injury. Causes severe eye irritation and Skin: Harmful if absorbed through the skin. Causes severe skin irritation and burns. Ingestion: May cause severe and permanent damage to the digestive tract. Causes digestive tract burns with immediate pain, swelling of the throat, convulsions, and possible coma. May cause central nervous system depression. Inhalation: May cause irritation of the respiratory tract with burning pain in the nose and throat, coughing, wheezing, shortness of breath and pulmonary edema. May cause asthmatic attacks due to allergic sensitization of the respiratory tract. Causes chemical burns to the respiratory tract. Vapors may cause dizziness or suffocation. Chronic: Prolonged or repeated skin contact may cause defatting and dermatitis. Laboratory experiments have resulted in mutagenic effects. Section 4 - First Aid Measures Eyes: Get medical aid immediately. Do NOT allow victim to rub eyes or keep eyes closed. Extensive irrigation with water is required (at least 30 Skin: Get medical aid immediately. Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Destroy contaminated shoes. Ingestion: Do not induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. Get medical aid immediately. Inhalation: Get medical aid immediately. Remove from exposure and move to fresh air immediately. If breathing is difficult, give oxygen. Do NOT use mouth-to-mouth resuscitation. If breathing has ceased apply artificial respiration using oxygen and a suitable mechanical device such as a bag and a mask. Notes to Physician: Treat symptomatically and supportively.

Section 5 - Fire Fighting Measures General Information: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NAIOSH (approved or equivalent), and full protective gear. Vapors may form an explosive mixture with air. Vapors can travel to a source of ignition and flash back. During a fire, irritating and highly toxic gases may be generated by thermal

```
PAGE: 2
                           07/18/06
                                                            ACCT:
                                                                               580773001
            DATE
            INDEX: D61958637
                                                            CAT NO: A258500
                                                                                                            PO NBR: NA
                      decomposition or combustion. Will burn if involved in a fire. Use
                     decomposition or combustion. Will burn if involved in a fire, Use water spray to keep fire-exposed containers cool. Water may be ineffective. Material is lighter than water and a fire may be spread by the use of water. Containers may explode in the heat of a fire. Flammable liquid and vapor. Vapors may be heavier than air. They can spread along the ground and collect in low or confined areas.
 Extinguishing Media:
                    Water may be ineffective. Do NOT use straight streams of water. Use water spray, dry chemical, carbon dioxide, or alcohol-resistant
                      foam.
Autoignition Temperature:513 deg C ( 955.40 deg F) Flash Point:51 deg C ( 123.80 deg F) Explosion Limits: Lower: 2.9 vol % Explosion Limits: Upper: 12.1 vol %
 NFPA Rating:
 health: 3; flammability: 2; instability: 0;
Section 6 - Accidental Release Measures
 General Information:
                    Use proper personal protective equipment as indicated in Section 8.
 Spills/Leaks:
                    Use water spray to dilute spill to a non-flammable mixture. Large spills may be neutralized with dilute alkaline solutions of soda ash (sodium carbonate, Na2CO3), or lime (calcium oxide, CaO). Avoid runoff into storm sewers and ditches which lead to waterways. Clean
                     up spills immediately, observing precautions in the Protective
Equipment section. Cover with sand, dry lime or soda ash and place
in a closed container for disposal. Remove all sources of ignition.
                    Use a spark-proof tool. Provide ventilation. A vapor suppressing foam may be used to reduce vapors.

Section 7 - Handling and Storage
 Handling:
                     Wash thoroughly after handling. Remove contaminated clothing and
                   wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Do not get in eyes, on skin, or on clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep container tightly closed. Keep away from heat, sparks and flame. Discard contaminated shoes. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Use only with adequate ventilation. Do not breathe vapor or mist.
                    mist
 Storage:
                    Keep container closed when not in use. Store in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area. Do not store in steel container. Section 8 - Exposure Controls, Personal Protection
 Engineering Controls:
                    Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust
                    ventilation to keep airborne concentrations below the permissible
                    exposure limits.
 Exposure Limits
        Chemical Name
                                                            ACGIH
                                                                                                   NIOSH
                                                                                                                              OSHA - Final PELs
                                                                                       -------
                                            10 ppm
                                                                                      10 ppm TWA: 30
    Propionic acid
                                                                                                                              none listed
                                                                                       mg/m3 TWA
 OSHA Vacated PELs:
Propionic acid:
10 ppm TWA; 30 mg/m3 TWA
Personal Protective Equipment
Eves:
                                               Wear chemical splash goggles.
Skin:
                                               Wear appropriate protective gloves to prevent skin
Clothing:
                                               Wear appropriate protective clothing to prevent skin
Respirators:
                                              A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use.
                                     Section 9 - Physical and Chemical Properties
Physical State:
                                                         Clear liquid
                                                         colorless, oily
Color:
Odor:
                                                         rancid odor - pungent odor
                                                         Acidic.
                                                         2 mm Hg @ 20 deg C
2.56 (air=1)
Vapor Pressure:
Vapor Density:
Evaporation Rate:
                                                         Not available
Viscosity:
Boiling Point:
                                                         1.175 cps @ 15 deg C
141 deg C ( 285.80&F)
-21 deg C ( -5.80&F)
 Freezing/Melting Point:
Decomposition Temperature:
                                                        Not available
Solubility in water:
                                                         Soluble
```

2,579

2,580

```
PAGE: 3
        DATE: 07/18/06
INDEX: D61958637
                                             ACCT:
                                                          580773001
                                             CAT NO: A258500 PO NBR: NA
                                            0.9942 @ 20/4&C
Specific Gravity/Density:
                                            CH3CH2COOH
Molecular Formula:
Molecular Weight:
                                            74.08
                                  Section 10 - Stability and Reactivity
 Chemical Stability:
                Stable under normal temperatures and pressures.
 Conditions to Avoid:
                Ignition sources, excess heat.
Incompatibilities with Other Materials
Strong oxidizing agents, strong bases, steel.
Hazardous Decomposition Products
Carbon monoxide, irritating and toxic fumes and gases, carbon
                dioxide.
 Hazardous Polymerization
Will not occur.
                                 Section 11 - Toxicological Information
 RTECS# :
 CAS# 79-09-4: UE5950000
LD50/LC50:
 RTECS: CAS# 79-09-4: Draize test, rabbit, eye: 990 ug
Severe; Oral, rat: LD50 = 2600 mg/kg; Skin, rabbit: LD50 =
500 uL/kg;
 Carcinogenicity:
           Propionic acid -
 Not listed as a carcinogen by ACGIH, IARC, NTP, or CA Prop 65.
 Epidemiology:
Medical reports of acute exposures of workers to propionic acid show mild to moderate skin burns, mild eye redness, and one case of mild cough and asthmatic response.
 Teratogenicity:
 No information found
 Reproductive:
 No information found
 Neurotoxicity:
No information found
 Mutagenicity:
 Not available
 Other:
 Not available
                                    Section 12 - Ecological Information
 Water flea Daphnia: TLm = 130 mg/L; 24 Hr; unspecifiedFish: Fathead Minnow: LC50 = 4740 mg/L; 96 Hr; Flow-through bioassay at 24.7 &C (pH 7.60)
                                   Section 13 - Disposal Considerations
 Chemical waste generators must determine whether a discarded chemical
 Chemical waste generators must determine whether a district chemical is classified as a hazardous waste.
US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate
 classification.
RCRA P-Series: None listed.
 RCRA U-Series: None listed.
                                     Section 14 - Transport Information
 US DOT
                                                PROPIONIC ACID
         Shipping Name:
Hazard Class:
                                                UN1848
         UN Number:
         Packing Group:
                                                TTT
 Canada TDG
         Shipping Name:
Hazard Class:
                                                PROPIONIC ACID
                                                UN1848
         UN Number:
 Packing Group: III USA RQ: CAS# 79-09-4: 5000 lb final RQ; 2270 kg final RQ
                                     Section 15 - Regulatory Information
 us Federal
          TSCA
  CAS# 79-09-4 is listed on the TSCA Inventory.
             Health & Safety Reporting List
the chemicals are on the Health & Safety Reporting List.
Chemical Test Rules
 None of
  None of the chemicals in this product are under a Chemical Test Rule.
 Section 12b
None of the chemicals are listed under TSCA Section 12b.
  None of the chemicals are issued under 15th Section 125. TSCA Significant New Use Rule
None of the chemicals in this material have a SNUR under TSCA.
 None of the chemicals in this material have a SNOR under CERCLA Hazardous Substances and corresponding RQs CAS# 79-09-4: 5000 lb final RQ: 2270 kg final RQ SARA Section 302 Extremely Hazardous Substances None of the chemicals in this product have a TPQ.
```

SARA Codes
CAS # 79-09-4: acute, flammable.
Section 313

No chemicals are reportable under Section 313.

Clean Air Act:
This material does not contain any hazardous air pollutants.
This material does not contain any Class 1 Ozone depletors.
This material does not contain any Class 2 Ozone depletors.

Clean Water Act: CAS# 79-09-4 is listed as a Hazardous Substance under the CWA CAS# /9-09-4 is listed as a Hazardous substance under the CWA. None of the chemicals in this product are listed as Priority Pollutants under the CWA. None of the chemicals in this product are listed as Toxic Pollutants under the CWA. OSHA: Propionic acid can be found on the following state right to know lists: California, New Jersey, Pennsylvania, Minnesota, STATE Massachusetts. California Prop 65 California No Significant Risk Level: None of the chemicals in this product are listed. European/International Regulations European Labeling in Accordance with EC Directives Hazard Symbols: C Risk Phrases: R 34 Causes burns. Safety Phrases: S 23 Do not inhale gas/fumes/vapour/spray. S 36 Wear suitable protective clothing.

S 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). WGK (Water Danger/Protection) CAS# 79-09-4: 1 Canada CAS# 79-09-4 is listed on Canada's DSL List Canadian WHMIS Classifications: B3, D1B, E
Canadian WHMIS Classifications: B3, D1B, E
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations. CAS# 79-09-4 is listed on Canada's Ingredient Disclosure List Section 16 - Other Information MSDS Creation Date: 5/05/1999 Revision #4 Date The information above is believed to be accurate and represents the The information above is believed to be accurate and represents the best information currently available to us. However, we make no best information currently available to us. However, we make no warranty of merchantibility or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages howsoever arising, even if the company has been advised of the possibility of such damages. possibility of such damages.

580773001

ACCT:

CAT NO: A258500

07/18/06

INDEX: D61958637

DATE:

PAGE: 4

PO NBR: NA

2,581