

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 2/24/2006
MSDS ARCHIVE

PAGE 1

SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

MANUFACTURERS NAME ADDRESS
W.M. BARR & COMPANY, INC. 2105 Channel Avenue
Memphis, TN 38113 USA

EMERGENCY TELEPHONE #1 EMERGENCY CONTACT
901-775-0100 W.M. Barr Technical Services

EMERGENCY INFORMATION
"3E" 24 HOUR MEDICAL EMERGENCY #, 800 451-8346.
SEE SECTION 5 FOR ADDITIONAL EMERGENCY INFORMATION

INVENTORY ITEM #
WCK73.1

PRODUCT NAME
EASYOFF DRIED LATEX PAINT RMVR

REVISED BY REVISION DATE
W.M. Barr Technical Services 11/19/1996

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE DESCRIPTION	PERCENT	CAS#	CARCINOGENICITY			
			NTP	ACGIH	OSHA	IARC
XYLENE	85- 90	1330-20-7	N	N	N	N
** ABOVE INGREDIENT CONSISTS OF THE FOLLOWING **						
ETHYL BENZENE	15- 20	100-41-4	N	N	N	N
XYLENE	80- 85	1330-20-7	N	N	N	N
ACETONE	10- 15	67-64-1	N	N	N	N
ETHYLENE GLYCOL MONOBUTYL ETHER	1- 5	111-76-2	N	N	N	N
NONYLPHENOXYPOLYETHOXYETHANOL	1- 5	9016-45-9	N	N	N	N

SECTION 3. REGULATORY INFORMATION

EXPOSURE LIMITS/REGULATORY INFORMATION

SUBSTANCE DESCRIPTION	REG. AGENCY U/M		TWA	STEL	CEIL	SKIN	PEL
	ACGIH	OSHA					
XYLENE	ACGIH	PPM	100.00	150.00	N/E	N	N/E
	OSHA	PPM	100.00	150.00	N/E	N	100.00
ETHYL BENZENE	ACGIH	PPM	100.00	125.00	N/E	N	N/E
	OSHA	PPM	100.00	125.00	N/E	N	100.00
XYLENE	ACGIH	PPM	100.00	150.00	N/E	N	N/E
	OSHA	PPM	100.00	150.00	N/E	N	100.00
ACETONE	ACGIH	PPM	500.00	750.00	N/E	N	N/E
	OSHA	PPM	N/E	N/E	N/E	N	1000.00
ETHYLENE GLYCOL MONOBUTYL ETHER	ACGIH	PPM	25.00	N/E	N/E	Y	N/E
	OSHA	PPM	N/E	N/E	N/E	Y	50.00
NONYLPHENOXYPOLYETHOXYETHANOL	ACGIH	PPM	N/E	N/E	N/E	N	N/E
	OSHA	PPM	N/E	N/E	N/E	N	N/E

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 2/24/2006
MSDS ARCHIVE

PAGE 2

SECTION 3. REGULATORY INFORMATION
(CONTINUED)

ADDITIONAL REGULATORY INFO

The time weighted average (TWA) value described herein is a threshold limit value (TLV) as established by ACGIH. The permissible exposure limit (PEL) is a value established by OSHA.

CALIFORNIA (PROPOSITION #65)

Ingredients in this product are not listed on California's Prop 65 list: "Chemicals Known to the State to Cause Cancer or Reproductive Toxicity."

SEC. 313 SUPPLIER NOTIFICATION

The following information must be included in all MSDS that are copied and distributed for this material.

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40CFR 372):

SUBSTANCE DESCRIPTION	PERCENT BY WEIGHT (UPPER LIMIT)	CAS#
XYLENE	90	1330-20-7
ETHYL BENZENE	18	100-41-4
XYLENE	77	1330-20-7
ACETONE	15	67-64-1

CLEAN AIR ACT

This formula contains no known ozone depleting chemicals.

HAZARD COMMUNICATION STANDARD

This document is prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200). This MSDS contains thirteen (13) sections.

The following effects and/or symptoms are not expected to be experienced by persons who use this product properly and according to ALL instructions, precautions, and warnings; however, should the product user experience ANY questionable effects or symptoms, the product user should immediately seek medical attention.

SECTION 4. HAZARDS IDENTIFICATION

INHALATION ACUTE EXPOSURE EFFECTS

Vapor harmful. May cause dizziness; headache; irritation of the respiratory tract; injuries to mucous membranes; watering of eyes; weakness; drowsiness; nausea; numbness in fingers, arms and legs; depression of the central nervous system; nasal discomfort and discharge; chest pain and coughing; vomiting; narcosis; liver and kidney injury; blood disorders; nose tumors; eye irritation; giddiness; anesthesia; confusion; olfactory changes; irregular heartbeat; unconsciousness; coma and death. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

SKIN CONTACT ACUTE EXPOSURE EFFECTS

Product may be absorbed through skin. Harmful if absorbed through skin. May cause irritation; drying of skin; defatting of skin; itching; redness; swelling; tissue damage; inflammation; discomfort or pain; numbness in fingers and arms; erythema. May be absorbed readily to produce symptoms similar to those listed under ingestion.

EYE CONTACT ACUTE EXPOSURE EFFECTS

This material is an eye irritant. May cause irritation; excess redness and swelling of the conjunctiva; excess blinking and tear production; temporary corneal effects. Causes severe irritation which is likely to lead to impairment or loss of vision.

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 2/24/2006
MSDS ARCHIVE

PAGE 3

SECTION 4. HAZARDS IDENTIFICATION
(CONTINUED)
-----**INGESTION ACUTE EXPOSURE EFFECTS**

Harmful or fatal if swallowed. May cause dizziness; headache; nausea; weakness; loss of coordination; irritation of mouth, throat and stomach; vomiting; gastrointestinal irritation; diarrhea; changes in white blood cells; salivation; pain, cough and hoarseness; and unconsciousness. Ingestion of significant quantities may result in red blood cell hemolysis. Liquid aspirated into lungs can cause chemical pneumonitis, which can be fatal.

CHRONIC EXPOSURE EFFECTS

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. May cause weakness; skin irritation; fatigue; numbness in hands and feet; permanent central nervous system changes; liver damage; kidney damage; blood disorders; and eye irritation. Prolonged skin contact may cause irritation; redness; swelling and possible tissue destruction. Prolonged or widespread contact may result in absorption of potentially harmful amounts of this material.

MEDICAL CONDITIONS AGGRAVATED

Diseases of the skin; liver and kidneys.

PRIMARY ROUTE OF EXPOSURE

Inhalation, ingestion, and dermal.

SECTION 5. FIRST AID MEASURES
-----**INHALATION**

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

SKIN CONTACT

Wash with soap and large quantities of water and seek medical attention if irritation from contact persists.

EYE CONTACT

Immediately flush with water for at least 15 minutes. Get medical attention.

INGESTION

Call your poison control center, hospital emergency room, or physician immediately for instructions.

NOTE TO PHYSICIAN

This formula is registered with POISINDEX.
Call your local poison control center for further information.

SECTION 6. FIRE FIGHTING MEASURES

HAZARD RATING SOURCE	HMIS	NFPA
HEALTH	2	1
FLAMMABILITY	3	3
REACTIVITY	0	0
OTHER	G	NA

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 2/24/2006
MSDS ARCHIVE

PAGE 4

SECTION 6. FIRE FIGHTING MEASURES
(CONTINUED)
-----**FLASH METHOD**

SETA - CLOSED CUP

FLASH POINT

43.00 F 6.11 C

LOWER EXPLOSION LIMIT

1.0

GENERAL COMMENTS

OSHA FLAMMABILITY: Class IB

EXTINGUISHING METHOD

Use carbon dioxide, dry powder, or foam.

FIRE FIGHTING PROCEDURES

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

FIRE AND EXPLOSION HAZARDS

DANGER! FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION. Do not smoke.

Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Beware of static electricity that may be generated by synthetic clothing and other sources.

SECTION 7. ACCIDENTAL RELEASE MEASURES
-----**CLEAN-UP**

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. SMALL SPILLS: take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable. LARGE SPILLS: dike far ahead of spill for later disposal.

For transportation related spills contact Chemtrec at 1-800-424-9300 for emergency assistance.

WASTE DISPOSAL

Dispose in accordance with applicable local, state and federal regulations.

SECTION 8. HANDLING AND STORAGE
-----**STORAGE**

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

HANDLING

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 2/24/2006
MSDS ARCHIVE

PAGE 5

SECTION 9. TRANSPORT INFORMATION
-----**TRANSPORTATION**

For D.O.T. information, contact W.M. Barr Technical Services
Department.

SECTION 10. EXPOSURE CONTROLS/PERSONAL PROTECTION
-----**VENTILATION PROTECTION**

Use only with adequate ventilation to prevent build-up of vapors.
Open all windows and doors. Use only with a cross ventilation of
moving fresh air across the work area. If strong odor is noticed or
you experience slight dizziness, headache, nausea, or eye-watering -
STOP - ventilation is inadequate. Leave area immediately.

RESPIRATORY PROTECTION

For OSHA controlled work place and other regular users - Use only
with adequate ventilation under engineered air control systems
designed to prevent exceeding appropriate TLV. For occasional use,
where engineered air control is not feasible, use properly main-
tained and properly fitted NIOSH approved respirator for organic
solvent vapors. A dust mask does not provide protection against
vapors.

SKIN PROTECTION

Wear impermeable gloves. Gloves contaminated with product
should be discarded. Promptly remove clothing that becomes soiled
with product.

EYE PROTECTION

Safety glasses, chemical goggles or face shields are recommended
to safeguard against potential eye contact, irritation, or injury.
Contact lenses should not be worn while working with chemicals.

OTHER PROTECTION

Various application methods can dictate use of additional protective
safety equipment, such as impermeable aprons, etc., to minimize
exposure. A source of clean water should be available in the work
area for flushing eyes and skin. Do not eat, drink, or smoke in the
work area. Wash hands thoroughly after use. Before reuse,
thoroughly clean any clothing or protective equipment that has been
contaminated by prior use. Discard any clothing or other
protective equipment that cannot be decontaminated, such as gloves
or shoes.

SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES

VOLATILE % 100
BY WEIGHT

BOILING POINT
GT 133.00 F 56.11 C BOILING RANGE - 133 F - 482 F

VAPOR DENSITY (Air = 1.0)
HEAVIER THAN AIR

EVAPORATION RATE
SLOWER THAN ETHER

BULK DENSITY
7.134
LBS/GAL AT 75 F

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 2/24/2006
MSDS ARCHIVE

PAGE 6

SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES
(CONTINUED)
-----**PH FACTOR**
N/E**PHOTOCHEMICALLY REACTIVE**
YES**MAX V.O.C.**
847 grams per liter (excluding exempt solvents and water)**MAX VAPOR PRESSURE**
(Of the V.O.C.)39mm Hg at 20 degrees C-----
SECTION 12. STABILITY AND REACTIVITY
-----**INCOMPATIBILITIES**
Incompatible with strong oxidizing agents; strong caustics; acids; alkali; nitric acid; amines; halogens; aldehydes; ammonia; and sulfuric acid.**DECOMPOSITION**
Thermal decomposition may produce carbon monoxide; and carbon dioxide.**POLYMERIZATION**
Will not occur.**STABILITY**
Stable.-----
SECTION 13. ADDITIONAL INFORMATION
-----**IMPORTANT NOTE**
The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.**LEGEND:**
PPM = parts per million
MG/M3 = milligrams per cubic meter
N/E or NE = none established
GT = greater than
N/A or NA = not applicable
TCC = tag closed cup
TOC = tag open cup
PMCC = Pensky-Martens closed cup
IDLH = Immediately Dangerous to Life and Health

END OF MSDS